

Pryda Stren-Joist

The Pryda Stren-Joist has been designed to allow holes to be cut in floor joists to enable pipes, wiring or other services to be passed through the joist. The fitting of a Pryda Stren-Joist re-instates the integrity of the penetrated joist.

Advantages:

- Quick and easy to install
- Fixing option of either nailing or screwing. Note—Fixing to the flooring must be done with screws provided. All other holes can use either nails or screws
- Can be retro-fitted. There is no requirement to remove services to fit the Stren-Joist
- Comes in one size, designed to fit 140—290mm joists
- Allows an easy solution to fix penetrations in floor joists made by other trades
- Timber grade can be MSG8 or better
- The edge of the penetration shall be at least the joist depth from the end of the joist
- All components are available in a single kit - **Pryda Code NPSJ**

Each kit contains: 1 x 'U' channel, 2 x arched angles, 1 x 500gm of Pryda Product Nails and 10 /8g x 20mm screws. (If the hex screw fixing option is used then 30 /12g x 35mm hex head type #17 galvanised screws are required. Not supplied)

Maximum Joist Penetration (mm)

Joist Size	Max Hole size
140x45	72
190x45	122
240x45	125
290x45	125

Note: Pryda Product nails (30x3.15mm) supplied with the kit are not to be substituted with nails of a lesser diameter such as standard clouts.